(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 16 June 2005 (16.06.2005)

PCT

(10) International Publication Number WO 2005/054317 A1

- (51) International Patent Classification⁷: C08F 283/00,
 290/06, G02B 1/04, C08F 283/02, C08L 51/08, 33/00,
 69/00
- (21) International Application Number:

PCT/NL2004/000828

(22) International Filing Date:

29 November 2004 (29.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: JP2003-408025

5 December 2003 (05.12.2003) J


- (71) Applicants (for all designated States except US): DSM IP ASSETS B.V. [NL/NL]; Het Overloon 1, NL-6411 TE Heerlen (NL). JSR JAPAN SYNTHETIC RUBBER CO., LTD. [JP/JP]; 5-6-10, Tsukiji Chuo-ku, Tokyo 104-8410 (JP). JAPAN FINE COATINGS CO., LTD. [JP/JP]; 57-1, Sawabe, Niiharimura, Niihari-gun, Ibaraki 300-4104 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): FUTAMI, Satochi

[JP/JP]; 5-6-10, Tsukiji Chuo-ku, Tokyo 104-8410 (JP). YAMAGUCHI, Yoshikazu [JP/JP]; 5-6-10, Tsukiji Chuo-ku, Tokyo 104-8410 (JP). TANABE, Takayoshi [JP/JP]; 5-6-10, Tsukiji Chuo-ku, Tokyo 104-8410 (JP).

- (74) Agent: G.C. HOOGENDAM; DSM Intellectual Property, P.O. Box 9, NL-6160 MA Geleen (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: PHOTOCURABLE COMPOSITION AND OPTICAL PART



$$-0 \xrightarrow{R^1} R^3 \xrightarrow{R^1} 0 - (II)$$

(57) Abstract: A photocurable composition comprising the following components (A) to (D): (A) at least one of the (meth)acrylates having the structures shown by the formulas: (I) and (II), wherein R¹ represents a hydrogen atom or a halogen atom excluding a fluorine atom, R² is a hydrogen atom, a halogen atom excluding a fluorine atom, Ph-C(CH₃)₂-, Ph-, or an alkyl group having 1-20 carbon atoms, and R³ represents -CH₂-, -S-, or -C(CH₃)₂-; (B) a (meth)acrylate having three or more functional groups, excluding the (meth)acrylates of the component (A); (C) a radical photoinitiator; and (D) a polycarbonate polyol having a hydroxyl value of 10-100; wherein 5-50 wt % of the total acrylic components in the composition are methacrylate compounds. A photocurable composition produces a cured product possessing a high refractive index, excelling in heat resistance, showing only a small amount of warping, and being particularly useful as an optical part such as a prism lens sheet.



WO 2005/054317 A1



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report